

Agilent Ref: 10010792-1
United States Application Serial No. 10/023,375

AMENDMENTS TO THE CLAIMS

1. **(Previously Presented)** A pulse jet printhead comprising:
 - (a) a multiple die printhead comprising:
 - (i) an orifice plate comprising a plurality of orifices; and
 - (ii) a plurality of thermal printhead dies each comprising a plurality of resistors and bonded to a surface of said orifice plate in operational alignment with said orifices to produce at least one firing chamber; and
 - (b) a volume of an aqueous fluid that includes a biopolymer or precursor thereof in said at least one firing chamber.
2. **(Original)** The pulse jet printhead according to Claim 1, wherein said printhead comprises from 2 to about 10 printhead dies.
3. **(Original)** The pulse jet printhead according to Claim 2, wherein said printhead comprises from 2 to 5 printhead dies.
4. **(Original)** The pulse jet printhead according to Claim 3, wherein said printhead comprises 3 printhead dies.
5. **(Previously Presented)** The pulse jet printhead according to Claim 1, wherein each of said printhead dies is a thermal pulse jet printhead die.
6. **(Original)** The pulse jet printhead according to Claim 1, wherein said biopolymer is selected from the group consisting of polypeptides and nucleic acids.
7. **(Original)** The pulse jet printhead according to Claim 1, wherein said precursor thereof is selected from the group consisting of amino acids and nucleotides.

Agilent Ref: 10010792-1

United States Application Serial No. 10/023,375

8. **(Original)** The pulse jet printhead according to Claim 1, wherein said printhead is present in a printhead assembly that further includes at least one fluid reservoir in fluid communication with said firing chamber.
9. **(Original)** The pulse jet according to Claim 8, wherein said fluid reservoir comprises said aqueous fluid that includes a biopolymer.
10. **(Previously Presented)** A pulse jet printhead assembly comprising:
(a) a multiple die printhead comprising:
(i) an orifice plate comprising a plurality of orifices; and
(ii) a plurality of thermal printhead dies each comprising a plurality of resistors and bonded to a surface of said orifice plate in operational alignment with said orifices to produce at least one firing chamber; and
(b) at least one fluid reservoir, wherein said fluid reservoir is in fluid communication with said firing chamber.
11. **(Original)** The pulse jet printhead assembly according to Claim 10, wherein said printhead comprises from 2 to about 10 printhead dies.
12. **(Original)** The pulse jet printhead assembly according to Claim 11, wherein said printhead comprises from 2 to 5 printhead dies.
13. **(Original)** The pulse jet printhead assembly according to Claim 12, wherein said printhead comprises 3 printhead dies.
14. **(Previously Presented)** The pulse jet printhead assembly according to Claim 10, wherein said pulse jet printhead assembly is a thermal pulse jet printhead assembly.
15. **(Original)** The pulse jet printhead assembly according to Claim 10, wherein said reservoir contains a volume of an aqueous fluid that includes a biopolymer or precursor thereof.

Agilent Ref: 10010792-1
United States Application Serial No. 10/023,375

16. **(Original)** The pulse jet printhead assembly according to Claim 15, wherein said biopolymer is selected from the group consisting of polypeptides and nucleic acids.

17. **(Original)** The pulse jet printhead assembly according to Claim 15, wherein said precursor thereof is selected from the group consisting of amino acids and nucleotides.

Claims 18.-28. **(Canceled)**

29. **(Original)** An automated pulse jet printing system, said system comprising a pulse jet printhead according to Claim 1.

30. **(Previously Presented)** A pulse jet printhead comprising:
(a) a multiple die printhead comprising:
 (i) an orifice plate comprising a plurality of orifices; and
 (ii) a plurality of thermal printhead dies each comprising a plurality of resistors and bonded to a surface of said orifice plate in operational alignment with said orifices to produce at least one firing chamber; and
(b) a volume of an aqueous fluid that includes nucleic acids or nucleotides in said at least one firing chamber.

31. **(Previously Presented)** The pulse jet printhead according to Claim 30, wherein said printhead comprises from 2 to about 10 printhead dies.

32. **(Previously Presented)** The pulse jet printhead according to Claim 31, wherein said printhead comprises from 2 to 5 printhead dies.

33. **(Previously Presented)** The pulse jet printhead according to Claim 32, wherein said printhead comprises 3 printhead dies.

Agilent Ref: 10010792-1
United States Application Serial No. 10/023,375

34. **(Previously Presented)** The pulse jet printhead according to Claim 30, wherein each of said printhead dies comprises a plurality of resistor elements on a surface of a semiconductor substrate.

35. **(Previously Presented)** The pulse jet printhead according to Claim 30, wherein said printhead is present in a printhead assembly that further includes at least one fluid reservoir in fluid communication with said firing chamber.

Please add the following new claims:

36. **(New)** The pulse jet printhead according to Claim 1, wherein said printhead dies are bonded to a single orifice plate.

37. **(New)** The pulse jet printhead assembly according to Claim 10, wherein said printhead dies are bonded to a single orifice plate.

38. **(New)** The pulse jet printhead according to Claim 30, wherein said printhead dies are bonded to a single orifice plate.

39. **(New)** The pulse jet printhead according to Claim 1, wherein said multiple printhead dies bonded to said orifice plate are parallel to each other.

40. **(New)** The pulse jet printhead assembly according to Claim 10, wherein said multiple printhead dies bonded to said orifice plate are parallel to each other.

41. **(New)** The pulse jet printhead according to Claim 30, wherein said multiple printhead dies bonded to said orifice plate are parallel to each other.